

Relaxation oscillations, stability, and cavity feedback in a superradiant Raman laser

Justin G. Bohnet,^{*} Zilong Chen, Joshua M. Weiner, Kevin C. Cox, and James K. Thompson
JILA, NIST and Department of Physics, University of Colorado, Boulder, Colorado 80309-0440, USA

We experimentally study the relaxation oscillations and amplitude stability properties of an optical laser operating deep into the bad-cavity regime using a laser-cooled ^{87}Rb Raman laser. By combining measurements of the laser light field with non-demolition measurements of the atomic populations, we infer the response of the the gain medium represented by a collective atomic Bloch vector. The results are qualitatively explained with a simple model. Measurements and theory are extended to include the effect of intermediate repumping states on the closed-loop stability of the oscillator and the role of cavity-feedback on stabilizing or enhancing relaxation oscillations. This experimental study of the stability of an optical laser operating deep into the bad-cavity regime will guide future development of superradiant lasers with ultranarrow linewidths.

PACS numbers: 42.50.Nn, 42.60.Rn, 42.55.Ye, 42.50.Pq

Optical lasers operating deep in the bad-cavity or superradiant regime, in which the cavity linewidth κ is much larger than the gain bandwidth $\gamma_{\perp}$, have attracted recent theoretical[1, 2] and experimental[3] interest. The interest has been partially driven by the possibility of creating spectrally narrow lasers with linewidths ≤ 1 millihertz and dramatically reduced sensitivity to the vibrations that limit state of the art narrow lasers and keep them from operating outside the laboratory environment[4]. These lasers may improve measurements of time[5], gravity[6], and fundamental constants[7, 8] aiding the search for physics beyond the standard model. The cold-atom Raman superradiant laser utilized here operates deep into the bad-cavity regime ($\kappa/\gamma_{\perp} \approx 10^3 \gg 1$), making it an important physics test-bed for fundamental and practical explorations of bad-cavity optical lasers.

In the interest of fundamental science and in light of the potential applications, it is important to understand the impact of external perturbations on lasers operating deep into the bad cavity regime. In this Letter, we present an experimental study of the response to external perturbations of the amplitude, atomic inversion, and atomic polarization of an optical laser operating deep into the bad-cavity regime. In contrast, experiments have extensively studied the amplitude stability properties of good-cavity lasers ($\kappa \ll \gamma_{\perp}$) (See Ref. [9] and references therein). Previous experimental work in the extreme bad cavity[3] and crossover regime[10] focused on the phase properties of the light and atomic medium. Amplitude oscillations, intensity noise, and chaotic instabilities have been observed in gas lasers operating near the cross-over regime ($\kappa/\gamma_{\perp} \leq 10$)[11–14]. Relaxation oscillations of the field have been studied deep into the bad cavity regime using masers[15] in which the radiation wavelength is comparable to the size of the gain medium, unlike in the present optical system. Previous theoretical studies of amplitude stability deep in the bad-cavity regime include studies of relaxation oscillations[16], chaotic instabilities[17],

and intensity fluctuations characterized by correlation functions[16, 18].

In good-cavity optical lasers, the atomic polarization (proportional to $J_{\perp}$) can be adiabatically eliminated and the relaxation oscillations are associated with the flow of energy back and forth between the gain inversion (proportional to J_z) and the cavity field A , where J_z , $J_{\perp}$ are components of the collective Bloch vector $\vec{J}$ describing the atomic gain medium. In contrast, in a bad-cavity laser, the cavity field can be adiabatically eliminated, and the oscillations are driven by the coupling of $J_{\perp}$ and J_z . Here, we will measure and infer not only the light field $A(t)$, but also the atomic degrees of freedom $J_{\perp}(t)$ and $J_z(t)$ using non-demolition cavity-aided measurements[19] to give the complete picture of the dynamics of relaxation oscillations in a bad-cavity laser.

We will also consider the effects on the laser's amplitude stability of non-ideal repumping through multiple intermediate states. Intermediate repumping states were not included in previous simple theoretical models[1], but are present in most actual realizations. In addition, we demonstrate that the cavity frequency tuning in response to the distribution of atomic population among various ground states can be used to suppress or enhance relaxation oscillations. As evidence, we show stabilization of J_z , $J_{\perp}$, and A similar to observations of the suppression of relaxation oscillations in good-cavity lasers[20]. The cavity frequency tuning mechanism is related to other applications of cavity feedback including the creation of nonlinearities for generating spin-squeezed atomic ensembles [21], cavity cooling and amplification in atomic and opto-mechanical systems [22], and the control of instabilities in gravitational wave detectors [23].

Our experimental system consists of a quasi-steady-state Raman laser described in Fig. 1 and in Ref. [3]. The laser uses $N = 1 \times 10^6$ to 2×10^6 ^{87}Rb atoms as the gain medium. The atoms are trapped and laser cooled into the Doppler-insensitive Lamb-Dicke regime ($40 \mu\text{K}$) in a 1-D optical lattice at 823 nm formed by a standing wave in a moderate finesse $F \approx 700$ optical cavity with




FIG. 1. (color online) (a), (b) Physical setup and energy level diagram. The trapping light (orange) and Raman dressing laser (red, power $\propto \Omega_d^2$) are injected along the cavity axis. The repumping light (purple, green) is applied perpendicular to the cavity axis. The emitted optical laser light (blue) is nearly resonant with the cavity mode (dashed lines) detuned from ω_{cav} by δ . The repumping is accomplished through a pair of two-photon transitions through intermediate optically excited states $|II\rangle$ and $|III\rangle$ with incoherent decay rates Γ . We individually control the two-photon rates W and Γ_3 with the repumping laser powers $\propto \Omega_{1,2}^2$. $|3\rangle$ represents other metastable ground states besides the laser levels. (c) Example emitted laser photon flux $|A(t)|^2$ versus time showing spiking and relaxation oscillations at turn-on.

a cavity power decay rate $\kappa/2\pi = 11$ MHz. The atom-cavity coupling to the relevant TEM_{00} cavity mode on resonance with the emitted light is characterized by the single particle cooperativity parameter of cavity-QED $C = 8 \times 10^{-3} \ll 1$.

Fig. 1b shows a simplified energy level diagram of a three level Raman laser system. The lasing transition is a spontaneous optical Raman transition from $|\uparrow\rangle \equiv |5^2S_{1/2} F=2, m_F=0\rangle$ to $|\downarrow\rangle \equiv |5^2S_{1/2} F=1, m_F=0\rangle$ induced by a dressing laser detuned from the $|\uparrow\rangle$ to $|I\rangle \equiv |5^2P_{1/2} F'=2\rangle$ transition by $\Delta/2\pi = +1.1$ GHz. The incoherent repumping process takes place through a third metastable ground state $|3\rangle$ which represents the sum of the other hyperfine ground states in ^{87}Rb . The full energy level diagram with details of the dressing and repumping lasers is provided in Ref. [24].

We control the dynamics of the system primarily through three two-photon population transfer rates: γ , W , and Γ_3 . We control γ (typical value 60 s^{-1}) using the intensity of the 795 nm dressing laser. We control the repumping rates W and Γ_3 using two 780 nm repumping lasers tuned near resonance with the $|5^2S_{1/2} F=1, 2\rangle \rightarrow |5^2P_{3/2} F'=2\rangle$ transitions. The repumping intensities are independently controlled allowing us to set the proportionality factor $r \equiv \Gamma_3/W$. In our experiments,

W ranges from 10^3 s^{-1} to 10^5 s^{-1} , and r ranges from 0.01 to 2. The repumping dominates all other homogeneous broadening of the $|\uparrow\rangle$ to $|\downarrow\rangle$ transition such that $\gamma_{\perp} \approx W/2$. The inhomogeneous broadening of the transition is $\gamma_{\text{in}} \approx 10^3 \text{ s}^{-1}$. To summarize, the relevant rates to characterize our system satisfy the hierarchy $\kappa \gg \gamma_{\perp} \approx W/2 \sim NC\gamma > \gamma_{\text{in}} \gg \gamma$. Coupling to other transverse and longitudinal cavity modes is negligible.

The frequency of the superradiantly emitted light ω_{γ} is set by the frequency of the dressing laser and the hyperfine splitting $\omega_{\text{HF}}/2\pi = 6.834$ GHz. The detuning of light and cavity resonance frequency is $\delta = 2(\omega_{\text{cav}} - \omega_{\gamma})/\kappa$, normalized to the cavity half linewidth. The single particle scattering rate from the dressing laser into the cavity mode is $\Gamma_c(\delta) = C\gamma/(1 + \delta^2)$.

The cavity frequency is dispersively tuned by the atomic ensemble $\omega_{\text{cav}} = \omega_{bcav} + \sum_k \alpha_k N_k$, where ω_{bcav} is the bare cavity frequency and α_k is the cavity frequency shift for a single atom in the k th ground Zeeman state resulting from dispersive phase shifts of the intracavity light field.

Since $\alpha_k \neq \alpha_j$ for $k \neq j$, the cavity frequency can provide a measurement of the populations N_k . We can suddenly switch off the repumping and dressing lasers to effectively freeze the atomic populations[25]. We then combine repeated non-demolition cavity frequency measurements[19, 26, 27] and NMR-like rotations[28] to determine $J_z(t) = \langle \frac{1}{2} \sum_i (|\uparrow_i\rangle \langle \uparrow_i| - |\downarrow_i\rangle \langle \downarrow_i|) \rangle$ and $\delta(t)$ [24]. The amplitude of the light field emitted from the cavity $A(t)$ just prior to freezing the system, along with the measurement of the cavity frequency detuning δ provides an inferred value of $J_{\perp} = \left| \langle \hat{J}_{-} \rangle \right|$ using the relation $A(t) = \sqrt{\Gamma_c(\delta(t))} J_{\perp}(t)$, where $\hat{J}_{-} = \sum_i^N |\downarrow_i\rangle \langle \uparrow_i|$.

We observe characteristic laser spiking and relaxation oscillation behavior in $|A(t)|^2$ as the laser turns on and settles to steady state (Fig. 1c). To systematically study small amplitude deviations about the steady-state values of $J_{z,s}$, A_s , and $J_{\perp,s}$, we apply a swept sine technique, similar to Ref. [29]. We apply a simultaneous small amplitude modulation of the repumping rates as $W(t) = W(1 + \epsilon \cos \omega t)$ and $\Gamma_3(t) = rW(t)$. The modulation frequency ω is scanned over frequencies of order W , such that $\gamma < \omega \ll \kappa$. We then measure and infer the quantities $A(t)$, $J_{\perp}(t)$, and $J_z(t)$ as described earlier.

To calculate the transfer function of the applied modulation, the measured light field amplitude $A(t)$ exiting the cavity as a function of time is fit to $A(t) = A_s(1 + a(\omega) \cos(\omega t + \phi_a(\omega)))$. The normalized fractional amplitude response transfer function is $T_A(\omega) \equiv a(\omega)/\epsilon$ and the phase response transfer function is $T_{\phi} \equiv \phi_a(\omega)$. We also define the modulation frequency that maximizes $T_A(\omega)$ as the resonance frequency ω_{res} . We present the results in Figs. 2, 3, and 4, which we discuss in detail after developing a theoretical model to guide the interpretation.




FIG. 2. (color online) (a) Parametric plots of the Bloch vector components $J_z(t)$ and $J_\perp(t)$ over a single cycle of modulation of the repumping rate W near W_{pk} for modulation frequencies below, near, and above resonance or $\omega/2\pi = 0.11, 2.2, 8$ kHz, from left to right. The black points are the measured small-signal deviations about the measured steady-state Bloch vector (red arrow). The blue curve is the predicted deviation from steady-state given the experimental parameters $N = 1.3 \times 10^6$, $r = 0.71$, $\delta_s = 1$, $W = 0.4NC\gamma$, and $NC\gamma = 125 \times 10^3 s^{-1}$. The modulation depth ϵ for data below and above resonance was doubled to make the response more visible. (b) The amplitude (upper) and phase (lower) response transfer functions $T_A(\omega)$, $T_\phi(\omega)$ of the light field for three values of the repumping rate W . The points are measured data, and the lines are zero free parameter predictions of the response. (inset) ω_{res} versus W (points) and a fit to ω_0 (line) showing the expected frequency dependence of the relaxation oscillations on repumping rate.

The theoretical model presented here consists of equations for the three ground state levels shown in Fig. 1b, which qualitatively describes the eight level ^{87}Rb system. The data is also quantitatively compared to an eight-level model described in Ref. [30]. Our theoretical model uses the semi-classical optical Bloch equations for an effective two level system where $\kappa \gg W, \gamma$ so that the cavity field is effectively slaved to the atomic polarization and can be adiabatically eliminated from the system of equations. Additionally, we have adiabatically eliminated the populations in the optically excited states $|I\rangle, |II\rangle, |III\rangle$, arriving at the steady state solutions for the inversion $J_{z,s}$ and collective atomic coherence $J_{\perp,s}$ [1, 31]. The steady state amplitude A_s is maximized

at $W = W_{pk} = \frac{1}{2}N\Gamma_c(\delta_s)$ where δ_s is the steady state cavity detuning.

To predict relaxation oscillations and damping, we do a straightforward expansion about the steady state values $J_{z,s}$ and $J_{\perp,s}$ as $J_z(t) \approx J_{z,s}(1 + j_z(t))$ and $J_\perp(t) \approx J_{\perp,s}(1 + j_\perp(t))$ and ignore terms that are second order in small quantities $j_\perp, j_z$ and repumping modulation amplitude ϵ [16, 32]. This results in a system of coupled differential equations for $j_z, j_\perp$ which can be recast as two uncoupled higher order differential equations

$$\beta \ddot{j}_{z,\perp} + \ddot{j}_{z,\perp} + 2\gamma_0 \dot{j}_{z,\perp} + \omega_0^2 j_{z,\perp} = D_{z,\perp}(\omega) \epsilon e^{i\omega t} \quad (1)$$

which, ignoring the third order term, is similar to the equation for a damped harmonic oscillator described by a damping rate γ_0 , a natural frequency ω_0 , and a complex, frequency dependent drive $D_{z,\perp}(\omega)$. To discuss the stability of the system, we also define the damping ratio $\zeta = \frac{\gamma_0}{\omega_0}$. At critical damping $\zeta = 1$, no relaxation oscillations are present, as the system exponentially relaxes to steady state.

We will consider relevant limiting cases of these equations to concisely guide the interpretation of the data. The full equations and expressions for γ_0 , ω_0 , β and $D_{z,\perp}(\omega)$ are given in Ref. [30].

First we consider the limiting case where $r \rightarrow \infty$ and $\delta = 0$ for which J_z and $J_\perp$ respond like a damped harmonic oscillator described by $\gamma_0 = W/2$ and $\omega_0 = \sqrt{W(NC\gamma - W)}$ as $\beta = 0$. However, the drive on the two oscillators is different, leading to different overall responses as $D_\perp(\omega) = \frac{W}{2}(NC\gamma - 2W - i\omega)$ and $D_z(\omega) = (NC\gamma - W)(W + i\omega)$. The magnitude and phase of the drives change with the modulation frequency and repumping rate, even as the modulation depth ϵ remains constant.

We show this driven oscillator response in Fig. 2a with the measured and predicted parametric plot of J_z and $J_\perp$ at three different applied modulation frequencies, with repumping near $W = W_{pk}$. Although the characteristic frequencies and rates of the atomic oscillator do not change, the differing drives lead to a change in the phase relationship between the response of the two quadratures. This data demonstrates how the external perturbation results in different effective drives for $j_\perp$ and j_z , leading to different behaviors with modulation frequency.

In Fig. 2b, we focus on the light field's transfer functions $T_A(\omega)$ and $T_\phi(\omega)$. Data for three different average repumping rates W are shown. The data qualitatively agrees with Eqn. 1, and quantitatively agrees with the displayed theory calculated for the full model including all ^{87}Rb levels.

In most experimental systems for a superradiant light source, the repumping ratio r is finite. In this case, the damping rate and resonance frequencies are $\gamma_0 = \frac{r(W(2r-1)+NC\gamma)}{2(1+r)(1+2r)}$ and $\omega_0 = \sqrt{\frac{r}{1+r}W(NC\gamma - W)}$. We can




FIG. 3. (color online) Effects of finite ratio of repumping rate r (a) Comparison at two values of r of $T_A(\omega)$ versus modulation frequency. The points are measured data in good agreement with the zero-free parameter fit (lines). (b) Plot of the resonance frequency ω_{res} (black) and the peak value $T_A(\omega_{\text{res}})$ (red) versus r .

understand the effect of the nonzero $\beta = \frac{1}{W(1+r)}$ on the response by considering the Fourier transform of Eqn. 1. The effective damping rate is the coefficient on the sum of the imaginary terms on the left hand side of Eqn. 1, $\gamma'_0 = \gamma_0 - \omega^2/(W(1+r))$. The frequency dependent term associated with β lowers the effective damping rate. However, as long as $\gamma'_0 > 0$ at $\omega = \omega_0$, the system will remain stable. The form of γ'_0 also indicates reduced damping for $r < 1$ as shown in Fig. 3a. We observe an increase in the peak relaxation oscillation amplitude as $r \rightarrow 0$ (red). From the form of ω_0 , we also expect to see the resonance frequency sharply decrease as $r \rightarrow 0$, which we observe in Fig. 3b (black).

To understand the dynamic tuning of the cavity resonance frequency ω_{cav} in response to changes in the atomic populations, we next consider the case $r \rightarrow \infty$ and $\delta \neq 0$. We also assume the cavity frequency is tuned by the atomic inversion J_z as $\alpha = \alpha_{\downarrow} = -\alpha_{\uparrow} > 0$. The dynamic cavity tuning then modifies the damping rate as $\gamma_0 = \frac{W}{2} \left(1 + 2\alpha\delta_s \left(\frac{N}{1+\delta_s^2} - \frac{W}{C\gamma} \right) \right)$. The tuning of ω_{cav} can act as either positive or negative feedback. When $\delta_s > 0$ the additional term enhances the damping, making the oscillator more stable. If $\delta_s < 0$, the damping can become negative, leading to an unstable oscillator.

We observe this qualitative behavior in the data, which agrees well with a full model[30]. As δ_s is varied from < 0 to > 0 , the cavity feedback first creates positive feedback that enhances and then negative feedback that decreases the measured amplitude response function $T_A(\omega)$ in Fig. 4a. We also measure the effect of the damping on $J_z(t)$ and $J_{\perp}(t)$ in Fig. 4b, where we can see that




FIG. 4. (color online) Evidence of negative and positive cavity feedback. (a) Amplitude transfer functions of the emitted electric field for three detunings from cavity resonance. The data points are the average of 4 experimental trials. The lines are fitted transfer functions with N as a free parameter. (b) Cavity damping of collective atomic degrees of freedom. The response going from $\delta_s = 0.2$ (left) where the γ_0 is small to $\delta_s = 0.9$ (right) where the system is expected to be critically damped. The red lines are sinusoidal fits to the data (circles). The dashed lines highlight the damping in both $J_{\perp}$ and J_z .

both atomic degrees of freedom are stabilized by negative cavity-feedback.

We have studied the dynamics of the polarization, inversion, and field of an optical laser operating deep in the bad-cavity regime. We have shown that dispersive cavity frequency tuning can suppress or enhance relaxation oscillations. Having experimentally validated our model for optical lasers in the extreme bad-cavity regime, future work can now extend the formalism to realistic models of proposed ultrastable lasers using ultranarrow atomic transitions in atoms such as Sr and Yb[1]. Further studies of the nonlinear dynamics of the extreme bad-cavity laser system will include investigations of chaos[17] and squeezed light generation[33].

The authors acknowledge helpful discussions with D. Meiser, M. J. Holland, J. Ye, D. Z. Anderson, and S. T. Cundiff. This work was funded by NSF PFC, NIST, ARO, and DARPA QuASAR. J.G.B. acknowledges support from NSF GRF, and Z.C. acknowledges support from A*STAR Singapore.

* Send correspondence to: bohnet@jilaui.colorado.edu

- [1] D. Meiser, J. Ye, D. R. Carlson, and M. J. Holland, Phys. Rev. Lett. **102**, 163601 (2009).
- [2] J. Chen, Chinese Science Bulletin **54**, 348 (2009).
- [3] J. G. Bohnet, Z. Chen, J. M. Weiner, D. Meiser, M. J. Holland, and J. K. Thompson, Nature **484**, 78 (2012).
- [4] Y. Y. Jiang, A. D. Ludlow, N. D. Lemke, R. W. Fox, J. A. Sherman, L.-S. Ma, and C. W. Oates, Nature Photon. **5**, 158 (2011).
- [5] A. D. Ludlow, T. Zelevinsky, G. K. Campbell, S. Blatt, M. M. Boyd, M. H. G. de Miranda, M. J. Martin, J. W. Thomsen, S. M. Foreman, J. Ye, T. M. Fortier, J. E. Stalnaker, S. A. Diddams, Y. Le Coq, Z. W. Barber, N. Poli, N. D. Lemke, K. M. Beck, and C. W. Oates, Science **319**, 1805 (2008).
- [6] C. W. Chou, D. B. Hume, T. Rosenband, and D. J. Wineland, Science **329**, 1630 (2010).
- [7] T. M. Fortier, N. Ashby, J. C. Bergquist, M. J. Delaney, S. A. Diddams, T. P. Heavner, L. Hollberg, W. M. Itano, S. R. Jefferts, K. Kim, F. Levi, L. Lorini, W. H. Oskay, T. E. Parker, J. Shirley, and J. E. Stalnaker, Phys. Rev. Lett. **98**, 070801 (2007).
- [8] S. Blatt, A. D. Ludlow, G. K. Campbell, J. W. Thomsen, T. Zelevinsky, M. M. Boyd, J. Ye, X. Baillard, M. Fouché, R. Le Targat, A. Brusch, P. Lemonde, M. Takamoto, F.-L. Hong, H. Katori, and V. V. Flambaum, Phys. Rev. Lett. **100**, 140801 (2008).
- [9] D. E. McCumber, Phys. Rev. **141**, 306 (1966).
- [10] S. J. M. Kuppens, M. P. van Exter, and J. P. Woerdman, Phys. Rev. Lett. **72**, 3815 (1994).
- [11] L. Casperson, IEEE J. of Quantum Electron. **14**, 756 (1978).
- [12] M. A. van Eijkelenborg, M. P. van Exter, and J. P. Woerdman, Phys. Rev. A **57**, 571 (1998).
- [13] R. G. Harrison and D. J. Biswas, Phys. Rev. Lett. **55**, 63 (1985).
- [14] C. O. Weiss, N. B. Abraham, and U. Hübner, Phys. Rev. Lett. **61**, 1587 (1988).
- [15] J. H. Shirley, American Journal of Physics **36**, 949 (1968).
- [16] M. I. Kolobov, L. Davidovich, E. Giacobino, and C. Fabre, Phys. Rev. A **47**, 1431 (1993).
- [17] H. Haken, Physics Letters A **53**, 77 (1975).
- [18] D. Meiser and M. J. Holland, Phys. Rev. A **81**, 063827 (2010).
- [19] Z. Chen, J. G. Bohnet, S. R. Sankar, J. Dai, and J. K. Thompson, Phys. Rev. Lett. **106**, 133601 (2011).
- [20] H. Statz, G. A. DeMars, D. T. Wilson, and C. L. Tang, Journal of Applied Physics **36**, 1510 (1965).
- [21] I. D. Leroux, M. H. Schleier-Smith, and V. Vuletić, Phys. Rev. Lett. **104**, 073602 (2010).
- [22] T. J. Kippenberg and K. J. Vahala, Science **321**, 1172 (2008).
- [23] L. Ju, D. G. Blair, C. Zhao, S. Gras, Z. Zhang, P. Barriga, H. Miao, Y. Fan, and L. Merrill, Classical and Quantum Gravity **26**, 015002 (2009).
- [24] “See supplemental material at [url will be inserted by publisher]”.
- [25] J. G. Bohnet, Z. Chen, J. W. Weiner, K. C. Cox, and J. K. Thompson, arXiv:1208.1710v2 [physics.atom-ph].
- [26] I. Teper, G. Vrijsen, J. Lee, and M. A. Kasevich, Phys. Rev. A **78**, 051803 (2008).
- [27] M. H. Schleier-Smith, I. D. Leroux, and V. Vuletić, Phys. Rev. Lett. **104**, 073604 (2010).
- [28] Z. Chen, J. G. Bohnet, J. M. Weiner, and J. K. Thompson, Review of Scientific Instruments **83**, 044701 (2012).
- [29] J. K. Wahlstrand, J. T. Willits, T. R. Schibli, C. R. Menyuk, and S. T. Cundiff, Opt. Lett. **32**, 3426 (2007).
- [30] “Manuscript in preparation”.
- [31] D. Meiser and M. J. Holland, Phys. Rev. A **81**, 033847 (2010).
- [32] A. E. Siegman, *Lasers*, 1st ed. (University Science Books, 1986).
- [33] A. Lambrecht, J. M. Courty, S. Reynaud, and E. Giacobino, Applied Physics B: Lasers and Optics **60**, 129 (1995).

Relaxation oscillations, stability, and cavity feedback in a superradiant Raman laser: supporting online material

Justin G. Bohnet, Zilong Chen, Joshua M. Weiner, Kevin C. Cox, and James K. Thompson
JILA, NIST and Department of Physics, University of Colorado, Boulder, Colorado 80309-0440, USA

PACS numbers: 42.50.Nn, 42.60.Rn, 42.55.Ye, 42.50.Pq




FIG. 5. (a) The energy level diagram for the D1 Raman transition used for lasing. The linearly polarized Raman dressing laser is shown in red and the superradiantly emitted light in blue. The cavity mode resonance frequency ω_{cav} is denoted with a blue dashed line. With the quantization axis defined by a 2.7 G magnetic field oriented along the cavity axis, the linearly polarized light is a linear combination of σ_+ and σ_- polarizations. (b) The energy level diagram for the D2 repumping beams F2 (green) and F1 (purple). The dark state with respect to the repumping lasers is labeled with a gray circle and corresponds to $|\uparrow\rangle$.

Cavity details, full energy level diagram, dressing, and repumping laser scheme.

The optical cavity has a mode waist of $71 \mu\text{m}$, mirror separation of 1.9 cm , and a finesse of $F = 700$. The atoms are trapped by a 1-D intracavity optical lattice at 823 nm and laser cooled to approximately $40 \mu\text{K}$. The sub-wavelength localization of the atoms along the cavity-axis ensures that the atoms are in the Lamb-Dicke regime along this direction. However, the atoms are not in the Lamb-Dicke regime with respect to motion transverse to the cavity axis.

We first note that the energy levels, dressing laser, repumping lasers, and relative frequency tunings are the same as the primary configuration presented in Ref. [1]. We include the details here again for clarity. The $|\downarrow\rangle \equiv |5^2S_{1/2} F=1, m_F=0\rangle$ and $|\uparrow\rangle \equiv |5^2S_{1/2} F=2, m_F=0\rangle$ hyperfine ground states of ^{87}Rb form the basis of our Raman laser (energy level dia-

gram shown in Fig. 5). The $|\uparrow\rangle$ state is dressed with an optical Raman laser at 795 nm that induces an optical decay to $|\downarrow\rangle$, with the cavity tuned to be resonant or near-resonant with the emitted light. The intensity of the dressing beam and the detuning by $\Delta/2\pi = +1.1 \text{ GHz}$ from the optically excited intermediate states $|I_{\pm}\rangle \equiv |5^2P_{1/2} F'=2, m'_F = \pm 1\rangle$ set the single-atom scattering rate into all of free space γ . The induced single-atom scattering rate into the cavity mode is $\Gamma_c = \frac{C\gamma}{1+\delta^2}$ where δ is the detuning of the cavity resonance frequency from the emitted light in units of the cavity half-linewidth, and C is the single particle cooperativity parameter of cavity QED[2]. The branching ratio for decay to $|\downarrow\rangle$ are included in the definition of C .

The quantization axis is set by a 2.7 G magnetic field along the cavity axis. The Raman dressing laser is injected non-resonantly along the cavity axis (experimental setup shown in Fig. 6a). For this quantization axis, the linearly polarized Raman dressing laser is an equal combination of σ^+ and σ^- light. Constructive interference between the two decay paths from $|\uparrow\rangle$ to $|\downarrow\rangle$ through the two states $|I_{\pm}\rangle$ leads to enhancement of light emission with linear polarization rotated 90° from the polarization of the dressing laser. Conversely, the orthogonal polarization of emitted light is suppressed by destructive interference of the two decay paths.

Two repumping lasers control the rate out of $|\downarrow\rangle$ and back into $|\uparrow\rangle$. The laser powers are independently set using acoustic optic modulators (AOMs) 1 and 2 shown in Fig. 6a. Both repumpers are π -polarized, applied perpendicular to the cavity, and separately tuned near the $|5^2S_{1/2} F=1, 2\rangle$ to $|5^2P_{3/2}, F'=2\rangle$ transitions. The F1 repumper moves atoms primarily from the ground $|5^2S_{1/2} F=1, m_F\rangle$ states to the ground $|5^2S_{1/2} F=2, m_F\rangle$ states, and sets the scattering rate W out of $|\downarrow\rangle$. The F2 repumper pushes population to $|\uparrow\rangle$ as the dipole matrix element for the transition $|5^2S_{1/2}, F=2, m_f=0\rangle \rightarrow |5^2P_{3/2}, F'=2, m'_f=0\rangle$ is zero. We quantify the F2 repumping rate by calculating the single particle scattering rate for an atom in $|5^2S_{1/2}, F=2, m_f=1\rangle$ state as Γ_3 . We define the pump ratio $r \equiv \frac{\Gamma_3}{W}$ to quantify to what degree population can build up in energy levels outside of $|\uparrow\rangle$ and $|\downarrow\rangle$, with the ideal repumping case being $r \rightarrow \infty$. Population will still remain in the states $|5^2S_{1/2}, F=1, m_f = \pm 1\rangle$ even as $r \rightarrow \infty$, unlike in the ideal three-level model. This is the




FIG. 6. Measurement setup and sequence timing diagram. (a) The physical setup for measuring the light field amplitude response $A(t)$ and the atomic responses $J_z(t)$, $J_\perp$ to a small modulation of the repumping rate $W(t)$. Optical beams are colored with arrows; RF and microwave signals are in black. (b) Timing diagram for measurements. Superradiance is started at t_1 , and the repumper $W(t)$ is modulated (with r constant) starting at time t_2 . At t_3 , the repumper and dressing lasers are shut off, freezing the atomic populations. The microwave π -pulse corresponds to a $12 \mu\text{s}$ pulse of 6.834 GHz microwaves resonant only with the ground hyperfine state transition $|\uparrow\rangle$ to $|\downarrow\rangle$. The pulse completely swaps the populations $N_\uparrow$ and $N_\downarrow$ of states $|\uparrow\rangle$ and $|\downarrow\rangle$. The cavity frequency probe windows M1 and M2 used to determine the dressed cavity frequency $\omega_{cav,1}$ and $\omega_{cav,2}$, and from which we can determine $J_z(t_3)$.

reason that the output power correction factor R does not asymptote to 1 as $r \rightarrow \infty$. Also note that unlike the simple three-level model, here, W includes Rayleigh scattering back to $|\downarrow\rangle$, contributing damping of the coherence $J_\perp$ without affecting the inversion J_z .

Response function measurement sequence

In the main text, we measure three quantities to characterize the response of the superradiant laser to small perturbations: the light field amplitude $A(t)$, the magnitude of the coherence $J_\perp(t)$, and the inversion $J_z(t)$. As shown in Fig. 6a and b, the perturbation is created by a small fractional modulation of the F1 and F2 repumping laser power at frequency ω such that $W(t) = W(1 + \epsilon \cos \omega t)$ while $r(t)$ remains constant. At time t_3 , we shut off the repumping and dressing lasers in less than 100 ns, freezing the atomic populations. The amplitude of the light just before shut off $A(t_3)$ is determined from the IQ-demodulated heterodyne signal shown in Fig. 6a.

We then use methods similar to those in [2] to non-destructively probe the cavity-mode to determine the cavity resonance frequency $\omega_{cav,1}$ and hence detuning from the emitted light frequency $\delta(t_3)$. We then calculate the coherence $J_\perp(t_3)$ using the relation $A(t_3) = J_\perp(t_3) \sqrt{C\gamma/(1 + \delta^2(t_3))}$. The probe is non-destructive in that a small fraction of the atoms are lost or Raman scattered to other states during the measurement.

The inversion $J_z(t_3)$ is determined by using a microwave π -pulse to swap the populations between $|\uparrow\rangle$ and $|\downarrow\rangle$, and then measuring the cavity resonance frequency a second time $\omega_{cav,2}$. Shifts in the cavity frequency due to atoms in other states are common mode to both measurements, such that the difference between the two cavity frequency measurements is only proportional to the inversion $\omega_{cav,1} - \omega_{cav,2} = 2(\alpha_\uparrow - \alpha_\downarrow)J_z$. The frequency

tuning of the cavity resonance per atom in each state $\alpha_{\uparrow,\downarrow}$ is calculated from the known cavity geometry, atomic dipole moments, and bare cavity detuning from resonance with nearby optical atomic transitions at 795 nm. The process is repeated for different stopping times t_3 in order to sample the modulation period for a set of times t_i . The data $J_z(t_i)$ versus $J_\perp(t_i)$ are shown in several parametric plots in the main text.

In the case of the field transfer functions $T_A(\omega)$ and $T_\phi(\omega)$, continuous time traces $A(t)$ are averaged over several trials at the same modulation frequency and phase to enhance signal to noise. The average response is then fit to $A(t) = A_s(1 + a(\omega) \cos(\omega t + \phi_A(\omega)))$, with transfer functions calculated as $T_A(\omega) = a(\omega)/\epsilon$ and $T_\phi(\omega) = \phi_A(\omega)$. The measurement is then repeated for different ω .

* Send correspondence to: bohnet@jilau1.colorado.edu

- [1] J. G. Bohnet, Z. Chen, J. M. Weiner, D. Meiser, M. J. Holland, and J. K. Thompson, *Nature* **484**, 78 (2012).
- [2] Z. Chen, J. G. Bohnet, S. R. Sankar, J. Dai, and J. K. Thompson, *Phys. Rev. Lett.* **106**, 133601 (2011).